



DRUM HEATER FOR PLASTIC DRUMS - HISD

ADVANTAGES

The drum heater for plastic drums mod. HISD ideal for reducing the viscosity of materials such as soap, grease, resins, paints that must be easily pumped or vacuumed.

Four models are available for 25L, 50L, 105L drums and for the most common 200L ones. All the models proposed have internal thermal insulation which increases thermal efficiency.

CONSTRUCTION

Produced with a fabric of excellent quality and extremely resistant, the heater incorporates a capillary thermostat 0-40 °C or 0-90 °C which allows excellent temperature control.

The HISD drum warmer is supplied with a simple and effective fastening system with traction belts for optimal installation.

CHARACTERISTICS

PLUS

- Teflon / polyester insulation
- Double insulated construction
- Capillary thermostat 0-40°C or 0-90°C
- Standard sizes: 25L, 50L, 105L, 200L
- Customized dimensions on request
- With thermal insulation
- Adjustable with traction belts
- Easy to install and fit
- Supplied with 4Mt H07RN-F power cable

TECHNICAL DATA

- Supply voltage: 110V or 230V
- Degree of protection IP40
- Mod.400mmx1020mm 200W 25L
- Mod.460mmx1250mm 250W 50L
- Mod.370mmx1650mm 400W 105L
- Mod.450mmx1950mm 450W 200L
- Mod.800mmx1950mm 1200W 200L



Certified organization TÜV AUSTRIA ITALIA S.P.A.
• ISO 9001:2015 with certificate n°Q-2523-17
• ISO 45001:2018 with certificate n°S-2523-19
• ISO 14001:2015 with certificate n°A-2523-24

